

6061-T651 ALUMINUM PLATE

Heat Treated & Aged, Stress-Relieved

Specifications: QQ-A-250/11, AMS 4027

| Thickness Inches | Width & Length | Estimated Wt. Lbs. Per Sheet |
|------------------------------------|-------------------------------|---------------------------------|
| .190 (2.70 lb. per sq. ft.) | 48 x 144 | 129.6 |
| .250 (3.53 lb. per sq. ft.) | 48.5 x 144.5 | 171.8 |
| .375 (5.29 lb. per sq. ft.) | 48 x 144 | 254.0 |
| .500 (7.06 lb. per sq. ft.) | 48.5 x 144.5 | 343.6 |

3003 ALUMINUM TREAD BRITE™ DECK PLATE



Conforms to ASTM B209

| Thickness Inches | Width & Length | Estimated Wt. Lbs. Per Sheet |
|--------------------------------------|---------------------------|---------------------------------|
| 0.063 (1.008 Lb. per sq. ft.) | 48 x 120 | 40.32 |
| .100 (1.57 lb. per sq. ft.) | 48 x 96 | 50.3 |
| | 48 x 192 | 100.5 |
| | 60 x 96 | 62.8 |
| | 60 x 192 | 125.7 |
| .125 (1.92 lb. per sq. ft.) | 36 x 108 | 51.3 |
| | 48 x 96 | 60.8 |
| | 48 x 120 | 76.0 |
| | 48 x 192 | 122.9 |
| | 60 x 96 | 76.8 |
| | 60 x 120 | 95.0 |
| | 60 x 192 | 153.7 |
| .188 (2.82 lb. per sq. ft.) | 48 x 96 | 90.3 |
| | 48 X 120 | 112.84 |
| | 48 x 192 | 180.5 |
| | 60 x 96 | 112.8 |
| | 60 x 120 | 141.0 |
| | 60 x 192 | 225.7 |
| .25 (3.671 lb. per sq. ft.) | 48 x 96 | 117.46 |
| | 48 x 192 | 234.92 |
| | 60 x 96 | 146.82 |
| | 60 x 120 | 183.53 |
| | 60 x 144 | 220.23 |
| | 60 x 192 | 293.65 |