

6061-T651 ALUMINUM PLATE

Heat Treated & Aged, Stress-Relieved

Specifications: QQ-A-250/11, AMS 4027

Thickness Inches	Width & Length	Estimated Wt. Lbs. Per Sheet
.190 (2.70 lb. per sq. ft.)		
	48 x 144	129.6
.250 (3.53 lb. per sq. ft.)		
	48.5 x 144.5	171.8
.375 (5.29 lb. per sq. ft.)		
	48 x 144	254.0
.500 (7.06 lb. per sq. ft.)		
	48.5 x 144.5	343.6

3003 ALUMINUM TREAD BRITE™ DECK PLATE



Conforms to ASTM B209

Thickness Inches	Width & Length	Estimated Wt. Lbs. Per Sheet
0.063 (1.008 Lb. per sq. ft.)		
	48 x 120	40.32
.100 (1.57 lb. per sq. ft.)		
	48 x 96	50.3
	48 x 192	100.5
	60 x 96	62.8
	60 x 192	125.7
.125 (1.92 lb. per sq. ft.)		
	36 x 108	51.3
	48 x 96	60.8
	48 x 120	76.0
	48 x 192	122.9
	60 x 96	76.8
	60 x 120	95.0
	60 x 192	153.7
.188 (2.82 lb. per sq. ft.)		
	48 x 96	90.3
	48 X 120	112.84
	48 x 192	180.5
	60 x 96	112.8
	60 x 120	141.0
	60 x 192	225.7
.25 (3.671 lb. per sq. ft.)		
	48 x 96	117.46
	48 x 192	234.92
	60 x 96	146.82
	60 x 120	183.53
	60 x 144	220.23
	60 x 192	293.65

6061-T6 TREAD PLATE

Diamond Pattern

Specification: MIL-F-17132

Conforms to ASTM B632



Thickness Inches	Width & Length	Estimated Wt. Lbs. Per Sheet
------------------	----------------	---------------------------------

.125 (1.92 lb. per sq. ft.)

48 x 96 64.0

48 x 192 128.0

.188 (2.82 lb. per sq. ft.)

48 x 96 90.2

48 x 192 180.5

.250 (3.672 lb. per sq. ft.)

48 x 96 117.5

48 x 192 235.0