

BLACK PIPE P.E.

Sch 40 - 21' Length,
ASTM A53

Size	OD	Wall	Wt./Ft.
1/8" . . .	0.405 . . .	0.068 . . .	0.24
1/4" . . .	0.540 . . .	0.088 . . .	0.42
3/8" . . .	0.675 . . .	0.091 . . .	0.56
1/2" . . .	0.840 . . .	0.109 . . .	0.85
3/4" . . .	1.050 . . .	0.113 . . .	1.13
1"	1.315 . . .	0.133 . . .	1.68
1-1/4" . .	1.660 . . .	0.140 . . .	2.27
1-1/2" . .	1.900 . . .	0.145 . . .	2.72
2"	2.375 . . .	0.154 . . .	3.65
2-1/2" . .	2.875 . . .	0.203 . . .	5.79
3"	3.500 . . .	0.216 . . .	7.58
3-1/2" . .	4.000 . . .	0.226 . . .	9.11
4"	4.500 . . .	0.237 . . .	10.79
5"	5.563 . . .	0.258 . . .	14.62
6"	6.625 . . .	0.280 . . .	18.97
8"	8.625 . . .	0.322 . . .	28.55
10"	10.750 . . .	0.365 . . .	40.48
12"	12.750 . . .	0.375 . . .	49.57

GALVANIZED PIPE P.E.

Sch 40 - 21' Length
ASTM A53

Size	OD	Wall	Wt./Ft.
1/4" . . .	0.540 . . .	0.088 . . .	0.42
3/8" . . .	0.675 . . .	0.091 . . .	0.56
1/2" . . .	0.840 . . .	0.109 . . .	0.85
3/4" . . .	1.050 . . .	0.113 . . .	1.13
1"	1.315 . . .	0.133 . . .	1.68
1-1/4" . .	1.660 . . .	0.140 . . .	2.28
1-1/2" . .	1.900 . . .	0.145 . . .	2.73
2"	2.375 . . .	0.154 . . .	3.68
2-1/2" . .	2.875 . . .	0.203 . . .	5.79
3"	3.500 . . .	0.216 . . .	7.57
3-1/2" . .	4.000 . . .	0.226 . . .	9.81
4"	4.500 . . .	0.237 . . .	10.79

EXTRA HEAVY BLACK PIPE P.E.

Sch 80 - 21' Length

Size	OD	Wall	Wt./Ft.
1/4" . . .	0.540 . . .	0.119 . . .	0.54
3/8" . . .	0.675 . . .	0.126 . . .	0.73
1/2" . . .	0.840 . . .	0.147 . . .	1.09
3/4" . . .	1.050 . . .	0.154 . . .	1.47
1"	1.315 . . .	0.179 . . .	2.17
1-1/4" . .	1.660 . . .	0.191 . . .	3.00
1-1/2" . .	1.900 . . .	0.200 . . .	3.63
2"	2.375 . . .	0.218 . . .	5.02
2-1/2" . .	2.875 . . .	0.276 . . .	7.66
3"	3.500 . . .	0.300 . . .	10.25
3-1/2" . .	4.000 . . .	0.318 . . .	12.51
4"	4.500 . . .	0.337 . . .	14.98
5"	5.563 . . .	0.375 . . .	20.78
6"	6.625 . . .	0.432 . . .	28.57

PIPE SIZE TUBING

Sch 40 - 21' Lengths

ASTM A500 Grade B

Size	OD	Wall	Wt./Ft.	Wt./21'
1/2" . . .	0.84	0.109 . . .	0.85 . . .	17.89
3/4" . . .	1.05	0.113 . . .	1.13 . . .	23.73
1"	1.31	0.133 . . .	1.68 . . .	35.28
1-1/4" . .	1.66	0.109 . . .	1.81 . . .	37.93
1-1/4" . .	1.66	0.135 . . .	2.27 . . .	47.67
1-1/2" . .	1.90	0.109 . . .	2.09 . . .	43.89
1-1/2" . .	1.90	0.145 . . .	2.72 . . .	57.12
2"	2.37	0.148 . . .	3.66 . . .	76.86
2-1/2" . .	2.88	0.203 . . .	5.79 . . .	121.59
3"	3.50	0.216 . . .	7.58 . . .	159.09
3-1/2" . .	4.00	0.226 . . .	9.12 . . .	191.52
4"	4.50	0.237 . . .	10.79 . .	226.60
5"	5.52	0.258 . . .	14.63 . .	307.23
6"	6.625 . . .	0.280 . . .	18.99 . .	398.79
8"	8.64	0.322 . . .	28.54 . .	599.51

Hot Rolled electric welded,
uncoated not pressure tested.

**CALL FOR LARGER SIZES
DIFFERENT SCHEDULES**

**Stainless Pipe - See Stainless Section
Aluminum Pipe - See Aluminum Section**