

# STAINLESS STEEL PLATE

No. 1 Finish - Hot Rolled,  
Annealed and Pickled, A480



Size in Inches	Lbs. Per Sq. Foot	Estimated Wt. Per Sheet
<b>3/16 x</b>		
48 x 96 . . . . .	8.580 . . . . .	274.56
48 x 120 . . . . .	8.580 . . . . .	343.20
60 x 120 . . . . .	8.580 . . . . .	429.00
<b>1/4 x</b>		
48 x 96 . . . . .	11.161 . . . . .	357.17
48 x 120 . . . . .	11.161 . . . . .	446.46
60 x 120 . . . . .	11.161 . . . . .	558.05
<b>3/8 x</b>		
48 x 96 . . . . .	16.497 . . . . .	527.89
48 x 120 . . . . .	16.497 . . . . .	659.87
<b>1/2 x</b>		
48 x 96 . . . . .	21.660 . . . . .	693.12
48 x 120 . . . . .	21.660 . . . . .	866.40

The Shearing Capacity of  
our 3/4" Plate Shear Decreases  
to 1/2" x 10' When Cutting  
Stainless Steel.

# STAINLESS FLOOR PLATE 304

ASTM A793 PATTERN B



Size in Inches	Lbs. Per Sq. Foot	Estimated Wt. Per Sheet
<b>1/8</b>		
36 x 120 . . . . .	6.15 . . . . .	184.51
48 x 120 . . . . .	6.15 . . . . .	246.01
<b>3/16</b>		
48 X 96 . . . . .	8.698 . . . . .	278.32
48 X 120 . . . . .	. . . . .	347.90
60 x 120 . . . . .	8.698 . . . . .	434.88
<b>1/4</b>		
48 X 120 . . . . .	. . . . .	450.03